

Product features

Undercounter dishwasher single skin 39x39 - 230 V		
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher




- Display type: 3 local display + diode bar
- Number of programs: 4
- Number of skin: 1
- Door clear height [mm]: 320
- Rack size [mm]: 390 x 390
- Water consumption of the washing cycle [l/basket]: 1,6
- Washing cycle time [s/basket]: 60-120-150
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011265	Boiler power [kW]	2.600
Net Width [mm]	436	Basin volume [l]	8
Net Depth [mm]	535	Tank power [kW]	0.600
Net Height [mm]	670	Water consumption of the washing cycle [l/basket]	1,6
Net Weight [kg]	31.00	Washing cycle time [s/basket]	60-120-150
Power electric [kW]	3.500	Door clear height [mm]	320
Loading	230 V / 1N - 50 Hz	Rack size [mm]	390 x 390
Boiler capacity [l]	2.60	Noise of device	61,5



Technical drawing

Undercounter dishwasher single skin 39x39 - 230 V		
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher





Product benefits

Undercounter dishwasher single skin 39x39 - 230 V		
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, partially pressed tub

- easy cleaning, high hygiene standard, long service life
- Washing arms with a component, common for washing and rinsing

washing arms made of composite material common arm for washing and rinsing integrated screw secured against falling out

- easy and safe handling during cleaning; higher user comfort
- LED Display

three-line display diode strip

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump
- Molded basket supports

guide rails for the baskets molded from the body of the dishwasher $\,$

- high hygiene standard
- longer service life

Detergent dispensers

two detergent and rinse aid dispensers

 precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath
- Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

cost saving



Technical parameters

Undercounter dishwasher sin	gle skin 39x39 - 230 V	
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher
1. SAP Code: 00011265		15. Number of programs: 4
2. Net Width [mm]: 436		16. Opening of device: Tilting down
3. Net Depth [mm]: 535		17. Door clear height [mm]: 320
4. Net Height [mm]: 670		18. Inlet pressure [bar]: 2-4
5. Net Weight [kg]: 31.00		19. Adjustable feet: Yes
6. Gross Width [mm]: 486		20. Number of skin:
7. Gross depth [mm]: 585		21. Self-cleaning cycle: Yes
8. Gross Height [mm]: 720		22. Boiler capacity [l]: 2.60
9. Gross Weight [kg]: 34.00		23. Boiler power [kW]: 2.600
10. Device type: Electric unit		24. Basin volume [l]:
11. Control type: Digital		25. Tank power [kW]: 0.600
12. Material: AISI 304		26. Number of arms for both rinsing and washing:
13. Power electric [kW]: 3.500		27. Arm connection: Hand loosen/tighten screw
14. Loading:		28. Washing arm type:

230 V / 1N - 50 Hz

Rotatable two-pronged



Technical parameters

Undercounter dishwasher sing	le skin 39x39 - 230 V	
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher
29. Washing arm material: Composite		42. Display type: 3 local display + diode bar
D. Rinsing arm type: Rotating two-pronged		43. USB port: Yes, for Firmware actualisation
Rinsing arm material: Composite		44. Self-diagnostics: Yes
2. Rack support: Pressed		45. Wash pump type: two-way - DuoFlow
3. Tank surface strainers: composite		46. Detergent dispenser: Yes
34. Drain filter: ArchiMedes - double filtration w ensures only 18% loss of clean v		47. Rinse aid dispenser: Yes
25. Thermostop: Yes		48. Water consumption of the washing cycle [l/basket]: 1,6
6. Boiler thermostat adjust: Yes		49. Washing cycle time [s/basket]: 60-120-150
77. Rack feed capacity: 24-30-60		50. Rinse water temperature [°C]: 65
8. Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump		51. Standard equipment for device: 2x glass basket, 1x cutlery basket
89. Energy Saving system: EnergySaving - Energy saving system due to lowering the boiler temperature		52. Program ProSpeed: Yes
10. Hot water electric valve: Yes		53. Program ProFessional: Yes
H1. Rack size [mm]:		54. Program ProTemp:

Yes

390 x 390



Technical parameters

Undercounter dishwasher single skin 39x39 - 230 V		
Model	SAP Code	00011265
QQI 42	A group of articles - web	Undercounter, continuous and black ware dishwasher

55. Program ProSelf:

Yes

58. Water supply connection:

3/4

56. Noise of device:

61,5

59. Diameter nominal:

DN 50

57. Cross-section of conductors CU [mm²]:

1