Technical data sheet

Product features

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher



- Display type: 3 local display + diode bar
- Number of programs: 5
- Number of skin: 1
- Door clear height [mm]: 450
- Rack size [mm]: 500 x 500
- Drain pump: No
- Water consumption of the washing cycle [l/basket]: 2,1
- Washing cycle time [s/basket]: 60-120-150
- Detergent and rinse pump system: Accurate dosing with a peristaltic pump
- Wash pump type: DuoFlow
- Drain filter: Double filtration with overflow discharge ensures only 18% loss of clean water to waste


SAP Code	00011268	**Boiler power [kW]**	8.000
Net Width [mm]	634	**Basin volume [l]**	15
Net Depth [mm]	744	**Tank power [kW]**	2.100
Net Height [mm]	1530	**Water consumption of the washing cycle [l/basket]**	2,1
Net Weight [kg]	90.00	**Washing cycle time [s/basket]**	60-120-150
Power electric [kW]	8.500	**Door clear height [mm]**	450
Loading	400 V / 3N - 50 Hz	**Rack size [mm]**	500 x 500
Boiler capacity [l]	6.00	**Noise of device**	60,4

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical drawing

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher



RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Product benefits

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

1 **Stainless steel outer shell construction**

round construction with stainless steel, rounded edges, partially pressed tub

- easy cleaning, high hygiene standard, long service life

2 **Washing arms with a component, common for washing and rinsing**

washing arms made of composite material
common arm for washing and rinsing
integrated screw secured against falling out

- easy and safe handling during cleaning; higher user comfort

3 **LED Display**

three-line display
diode strip

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4 **Double pump**

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5 **Molded basket supports**

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6 **Detergent dispensers**

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7 **Double filter system**

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8 **Energy saving**

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

1. **SAP Code:**
   00011268
2. **Net Width [mm]:**
   634
3. **Net Depth [mm]:**
   744
4. **Net Height [mm]:**
   1530
5. **Net Weight [kg]:**
   90.00
6. **Gross Width [mm]:**
   774
7. **Gross depth [mm]:**
   868
8. **Gross Height [mm]:**
   1579
9. **Gross Weight [kg]:**
   100.00
10. **Device type:**
    Electric unit
11. **Control type:**
    Digital
12. **Material:**
    AISI 304
13. **Power electric [kW]:**
    8.500
14. **Loading:**
    400 V / 3N - 50 Hz
15. **Additional information:**
    Also possible: 230 V / 3N or 230 V / 1N (must be specified when ordering)
16. **Rack size [mm]:**
    500 x 500
17. **Number of programs:**
    5
18. **Opening of device:**
    Flip up
19. **Door clear height [mm]:**
    450
20. **Inlet pressure [bar]:**
    2-4
21. **Adjustable feet:**
    Yes
22. **Number of skin:**
    1
23. **Boiler capacity [l]:**
    6.00
24. **Boiler power [kW]:**
    8.000
25. **Basin volume [l]:**
    15
26. **Tank power [kW]:**
    2.100
27. **Number of arms for both rinsing and washing:**
    2
28. **Arm connection:**
    Hand loosen/tighten screw

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

29. Washing arm type:
Rotatable two-pronged

30. Washing arm material:
Composite

31. Rinsing arm type:
Rotating two-pronged

32. Rinsing arm material:
Composite

33. Deep drawn tank:
Yes

34. Tank surface strainers:
composite

35. Drain filter:
Double filtration with overflow discharge ensures only 18% loss of clean water to waste

36. Thermostop:
Yes

37. Boiler thermostat adjust:
Yes

38. Rack feed capacity:
24-30-60

39. Detergent and rinse pump system:
Accurate dosing with a peristaltic pump

40. Energy Saving system:
Energy saving system due to lowering the boiler temperature

41. Hot water electric valve:
Yes

42. Display type:
3 local display + diode bar

43. Location of control panel:
Down

44. USB port:
Yes, for Firmware actualisation

45. Drain pump:
No

46. Self-diagnostics:
Yes

47. Wash pump type:
DuoFlow

48. Detergent dispenser:
Yes

49. Rinse aid dispenser:
Yes

50. Water consumption of the washing cycle [l/basket]:
2,1

51. Washing cycle time [s/basket]:
60-120-150

52. Rinse water temperature [°C]:
80

53. Standard equipment for device:
1x glass basket, 1x plate basket, 1x cutlery basket

54. Program ProSpeed:
Yes

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062

Technical data sheet

Technical parameters

Hood type dishwasher single skin 50x50 400 V / 3N		
Model	**SAP Code**	00011268
QQI 102	**A group of articles - web**	Undercounter, continuous and black ware dishwasher

55. Program ProFessional:
Yes

56. Program ProTemp:
Yes

57. Program ProSelf:
Yes

58. Program ProLong:
Yes

59. Noise of device:
60,4

60. Cross-section of conductors CU [mm²]:
1,5

61. Water supply connection:
3/4”

62. Diameter nominal:
DN 50

RM GASTRO, s.r.o.,
Třída Čs. armády 816,
391 81 Veselí nad Lužnicí 1, ID:49825062