

Technical data sheet

Product features



Hot dog roller grill roller 8 rollers

Model	SAP Code	00000407
CW 8	A group of articles - web	Sausage warmers



- Material: Stainless steel
- Indicators: operation and warm-up
- Minimum device temperature [°C]: 80
- Maximum device temperature [°C]: 300
- Number of internal parts: 7
- Tubes length [mm]: 320

SAP Code	00000407	Power electric [kW]	1.800
Net Width [mm]	460	Loading	230 V / 1N - 50 Hz
Net Depth [mm]	350	Number of internal parts	7
Net Height [mm]	200	Minimum device temperature [°C]	80
Net Weight [kg]	11.00	Maximum device temperature [°C]	300

Technical data sheet

Technical drawing



Hot dog roller grill roller 8 rollers

Model	SAP Code	00000407
CW 8	A group of articles - web	Sausage warmers

Technical data sheet



Product benefits

Hot dog roller grill roller 8 rollers

Model	SAP Code	00000407
CW 8	A group of articles - web	Sausage warmers

1

All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design
- resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning

2

Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows the on/off, heating/ non-heating state of the appliance

3

Positionable power switch

adjustable roll rotation

- Ideal toasting of sausages according to the customer's wishes

4

Encapsulated heaters inside the roll

no-bake rolls
uniform heating of the roll

- better output quality of sausages

Technical data sheet



Technical parameters

Hot dog roller grill roller 8 rollers

Model	SAP Code	00000407
CW 8	A group of articles - web	Sausage warmers

1. SAP Code:

00000407

2. Net Width [mm]:

460

3. Net Depth [mm]:

350

4. Net Height [mm]:

200

5. Net Weight [kg]:

11.00

6. Gross Width [mm]:

400

7. Gross depth [mm]:

510

8. Gross Height [mm]:

250

9. Gross Weight [kg]:

12.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Material:

Stainless steel

13. Power electric [kW]:

1.800

14. Loading:

230 V / 1N - 50 Hz

15. Minimum device temperature [°C]:

80

16. Maximum device temperature [°C]:

300

17. Protection of controls:

IPX4

18. Number of internal parts:

7

19. Tubes length [mm]:

320

20. Number of revolutions / min:

0

21. Indicators:

operation and warm-up

22. Cross-section of conductors CU [mm²]:

0,5