

Product features

Combi convection steam oven electric 10x GN 1/1 direct steam touch screen right door		
Model	SAP Code	00038909
MPDN 1011 ER	A group of articles - web	Convection machines



- Steam type: Injection
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1, EN 600x400
- GN device depth: 65
- Control type: Touchscreen
- Display size: 7"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00038909	Steam type	Injection
Net Width [mm]	907	Number of GN / EN	10
Net Depth [mm]	752	GN / EN size in device	GN 1/1, EN 600x400
Net Height [mm]	1023	GN device depth	65
Net Weight [kg]	110.00	Control type	Touchscreen
Power electric [kW]	12.600	Display size	7"
Loading	400 V / 3N - 50 Hz		



Technical drawing

Combi convection steam oven electric 10x GN 1/1 direct steam touch screen right door		
Model	SAP Code	00038909
MPDN 1011 ER	A group of articles - web	Convection machines



Product benefits

Combi convection steam oven electric 10x GN 1/1 direct steam touch screen right door		
Model	SAP Code	00038909
MPDN 1011 ER	A group of articles - web	Convection machines

Rapid chamber ventilation system

fast ventilation of odors

- saving time and costs

Double glazed ventilation door (panels can be opened)

easy cleaning and washing

- easier human work and effort - more satisfied staff

LED cooking chamber lighting

overview inside the combi oven

 saving time and costs, when we do not open the convection oven, hot air does not escape

AISI 304 cooking chamber with curved corners easy cleaning and washing

- easier human work and effort - more satisfied staff

Height adjustable feet variability of operation

- possibility of height adjustment

Single knob control simplicity

saving time; easier human work and effort - more satisfied staff

Trolley
cooks and handles up to 20 GN at once

- low operating costs, saving time and costs

Preset cooking programs

possibility of controlling 9 cooking phases for each of them

- saving time and costs

One Touch cooking mode
immediate start of the cooking cycle "one touch of the program"

- saving time and costs

Easy service

possibility of cooking different dishes at the same time

saving time and costs

Super Steam

possibility of setting 2 humidity levels

- tasty balanced meals

Hold function

possibility of maintaining food temperature, immediate serving

saving time and costs

Regeneration function

food regeneration

tasty and more valuable food, nice appearance of the food.

Rack control

possibility of serving all dishes at the same time in one place

- saving time and costs



Technical parameters

Combi convection steam oven ele	ctric 10x GN 1/1 direc	t steam touch screen right door
Model	SAP Code	00038909
MPDN 1011 ER	A group of articles - web	Convection machines
1. SAP Code: 00038909		14. Exterior color of the device: Stainless steel
2. Net Width [mm]: 907		15. Adjustable feet: Yes
3. Net Depth [mm]: 752		16. Humidity control: Yes, indirect measuring
4. Net Height [mm]: 1023		17. Stacking availability: Yes
5. Net Weight [kg]: 110.00		18. Control type: Touchscreen
6. Gross Width [mm]: 940		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 900		20. Steam type: Injection
8. Gross Height [mm]: 1078		21. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 130.00		22. Delayed start: Yes
10. Device type: Electric unit		23. Display size: 7"
11. Power electric [kW]: 12.600		24. Delta T heat preparation: Yes
12. Loading: 400 V / 3N - 50 Hz		25. Unified finishing of meals EasyService: Yes
13. Material: AISI 304		26. Night cooking: Yes



Technical parameters

Combi convection steam oven el	ectric 10x GN 1/1 dire	ct steam touch screen right door
Model	SAP Code	00038909
MPDN 1011 ER	A group of articles - web	Convection machines
27. Multi level cooking: Drawer program - control of heat dish separately	treatment for each	41. Interior lighting: Yes
28. Advanced moisture adjustmen	t:	42. Low temperature heat treatment: Yes
29. Slow cooking: from 50 °C		43. Number of fans:
30. Fan stop: Interruption when door is opened	l, not braked	44. Number of fan speeds:
31. Lighting type: LED lighting in the door, on one si	ide	45. Number of programs: 1000
32. Cavity material and shape: AISI 304, with rounded corners for	reasy cleaning	46. USB port: Yes, for uploading recipes and updating firmware
33. Reversible fan: Yes		47. Door constitution: Vented safety double glass, removable for easy cleaning
34. Sustaince box: Yes		48. Number of preset programs: 100
35. Standard equipment for device 1-point probe	e:	49. Number of recipe steps: 9
36. Heating element material: Incoloy		50. Minimum device temperature [°C]: 50
37. Probe: Yes		51. Maximum device temperature [°C]: 300
38. Shower: Manual (optional)		52. Device heating type: Combination of steam and hot air
39. Distance between the layers [r	nm]:	53. HACCP: Yes
40. Smoke-dry function:		54. Number of GN / EN:

10

Yes



Technical parameters

Combi convection steam oven electric 10x GN 1/1 direct steam touch screen right door			
Model	SAP Code	00038909	
MPDN 1011 ER	A group of articles - web	Convection machines	
55. GN / EN size in device: GN 1/1, EN 600x400		58. Cross-section of conductors CU [mm ²]: 4	
-			_